

Material Preparation

Apply only to clean, dry surfaces. Keep container closed when not in use. Do Not Thin.

Surface Preparation

All surfaces should be thoroughly cleaned to remove all mold, dust and loose particles. All weathered wood should be lightly sanded before application of **BLAZEGUARD Fire-Retardant Paint**.

Application

Always ensure adequate ventilation. Caulk all joint gaps 1/8" wide or greater before coating application. Apply **BLAZEGUARD Fire-Retardant Paint** to all surfaces by brush, roller, or airless spray at a rate of not greater than 120 ft²/gal. Under normal circumstances an application can be completed in one coat, but for extremely porous or irregular surfaces, a second coat may be required. Ensure the finished surface is well sealed. For airless spray application use an electric 30:1 unit with a 0.015-0.021 fluid tip and 800-900psi gun atomizing pressure.

Clean -Up

Use fresh water to clean brushes and paint rollers before product dries. Flush spray equipment with a cleaning solution of ½ cup pine oil cleanser, ½ cup sudsy ammonia and four (4) gallons of water. Flush until material exiting pump shows no evidence of **BLAZEGUARD Fire-Retardant Paint**. Dry product may be removed with solvents such as chlorinated solvents, or undiluted pine oil or citrus based cleansers.

Limitations

Store and apply between 40°F and 100°F. Protect from freezing.

Product shelf life is approximately one (1) year when stored between 40°F and 100°F.

For exterior use top coat with a high quality exterior latex paint after 48 hours (minimum) dry time.

Keep out of reach of children.