

***Material Preparation***

Stir well. Apply only to clean, dry surfaces. Keep container closed when not in use. Do Not Thin.

***Surface Preparation***

All surfaces should be thoroughly cleaned to remove all mold, dust and loose particles. Pre-clean and disinfect mold or mildew contaminated surfaces.

***Application***

Apply uniformly to wooden or gypsum wall board surfaces at a rate of 500-700ft<sup>2</sup>/gal until a thin uniform film remains on the surface. OSB and weathered wood requires more than new wooden surfaces. On hard non-porous surfaces such as hardwoods or finished concrete it can be used up to 800 ft<sup>2</sup>/gal. **MYCOGUARD** can be sprayed with any airless equipment using a .13-.17 mil spray tip.

***Over Coating***

Allow **MYCOGUARD** to dry completely before over coating, with a minimum dry time of one (1) hour. A single coat is all that is required, but two coats will provide better hid and whiteness. On exterior applications over bare wood use two coats for 200-300 ft<sup>2</sup>/gallon total coverage rate.

***Clean -Up***

Use fresh water to clean brushes and paint rollers before product dries. Flush spray equipment with a cleaning solution of ½ cup pine oil cleanser, ½ cup sudsy ammonia and four (4) gallons of water. Flush until material exiting pump shows no evidence of **MYCOGUARD**. Dry product may be removed with solvents such as chlorinated solvents, lacquer thinner or undiluted pine oil or citrus based cleansers.

***Limitations***

Store and apply between 40°F and 100°F. Protect from freezing.

Product shelf life is approximately one (1) year when stored between 40°F and 100°F.

Keep out of reach of children.

This product does not protect the user or others against bacteria, viruses, germs, or other disease organisms.

(320) 764.5797 *main*      510 4<sup>th</sup> Street North  
(320) 764.5799 *fax*        P.O. Box 379  
(800) 638.4570 *toll free*    Watkins, MN 55389 USA